

SpectraGuard™ 360 is a high performance blended antiscalant/dispersant with broad spectrum scale inhibition, enabling stable stable performance by complete control of the feed water chemistry. Capable of controlling carbonates, sulfates, phosphates, metal hydroxides, silica and particulates, SpectraGuard™ 360 provides full protection of the membrane system from a multitude of feed waters. The superior performance of this product enables lower dosage rates to provide the same control as traditional phosphonate chemistries.

Features / Benefits

- Using a proprietary blend of polymers and phosphonates this formula provides added control of membrane fouling in waters with high salts, high silica and colloidal foulants
- Higher performance allows for lower dose rates than existing formulations
- Stable molecular structure maintains integrity in high pH, high temperature and high salinity applications
- Classified for use in membrane systems producing drinking water (ANSI/NSF Standard 60)

Uses

- Control of calcium carbonate, calcium sulfate, barium sulfate, calcium fluoride, silica, and hydroxides of iron and manganese

Specifications

Appearance	Amber liquid
pH (1% solution)	2.00 – 2.80
Density (kg/liter)	1.00 – 1.20



Packaging

Pail: 5 gallon/18.9 liter

Tote: 275 gallon/1,040 liter

Drum: 55 gallon/208 liter

Bulk: available upon request

For special packaging options, please contact PWT or your local distributor.

SpectraGuard™ 360
 LIQUID REVERSE OSMOSIS ANTISCALANT

SpectraGuard™ 360

LIQUID REVERSE OSMOSIS ANTISCALANT

General Mixing & Application Instructions for SpectraGuard™ 360

1. Typical dose rates are 1.0 to 5.0 mg/l
2. Contact Professional Water Technologies™ or your local distributor for custom chemical dosing recommendation

ProDose XPRT™ – Scaling Prediction Software

ProDose XPRT™ uses the most accurate scaling prediction calculations available to accurately determine effective antiscalant dosage, and cleaning chemical usage. The user can enter multiple cases to study various operating conditions, directly enter concentrate analysis, and select the best PWT product and dosage for the application.

ProDose XPRT™ is available upon request only. Please contact your PWT representative for more information.

The screenshot displays the PWT ProDose software interface. At the top, there is a navigation bar with the PWT logo and several tabs: UNITS (US), TEMPERATURE (Fahrenheit), PERMEATE FLOW (81.00), RECOVERY (75.0%), ANTISCALANT (SpectraGuard Liquid), DOSAGE (2.95 PPM), SOURCE (Well Water), PROJECT NAME (Project 1), and CASE (1). Below this, a sidebar on the left contains icons for PROJECT INFORMATION, WATER QUALITY, SYSTEM INFORMATION, CHEMICAL SELECTION, CALCULATIONS, and REPORT. The main content area is divided into several sections: OVERVIEW (with fields for CLIENT NAME, PROJECT NAME, LOCATION, PREPARED BY, DATE, and WATER TYPE), MEASUREMENTS (with dropdowns for PRESET UNITS, TEMPERATURE, FLOW RATES, and MASS UNITS), COMMENTS (OPTIONAL) (a large text area), and TOTAL CASES (1 AVAILABLE) (a table with columns for Cases and Modified Date). The table shows one case with ID 1 and a modified date of 5/27/2016. Below the table is a section for Selected Case Description.