



# SW 400 R G2

Industry-leading seawater RO membrane with balanced salt rejection and productivity

## Key Features

- Superior salt rejection
- High boron rejection
- High permeate flow rate
- Improved fouling resistance due to thicker feed spacer

## Main Benefits

- A combination of high permeate water quality and energy efficiency

## Ideal Applications

- Single and multi-pass SWRO design requiring balanced permeate water quality and energy efficiency



**Headquarter:** 54/18 Bui Quang La, An Hoi Tay Ward, HCMC, Vietnam

**Branch:** 77 Dong Hung Thuan 10B, Dong Hung Thuan Ward, HCMC, Vietnam

**Phone:** (028) 6258 5368 – (028) 6291 9568

**Email:** info@atswatertechnology.com

**Website:** www.atswatertechnology.com



Homepage



LinkedIn



Youtube



This product is certified to NSF/ANSI/CAN Standard 61 for drinking water systems

D-SW400RG2-EN-013026

## Benefits of NANO H2O SW G2 membrane

- ▶ Better permeate quality without increasing operating pressure
- ▶ Lower energy costs without reducing permeate quality
- ▶ Reduced CAPEX and OPEX for multi-pass SWRO systems


## Performance Specifications

Item	Unit	Value
Permeate Flow Rate	GPD (m <sup>3</sup> /d)	9,000 (34.1)
Stabilized Salt Rejection	%	99.88
Minimum Salt Rejection	%	99.75
Stabilized Boron Rejection	%	93
Active Membrane Area	ft <sup>2</sup> (m <sup>2</sup> )	400 (37)
Feed Spacer Thickness	mil	34

The specifications outlined above are normalized performances based on the following test conditions:

- **Test Condition:** 32,000 ppm NaCl, 5 ppm Boron, 800 psi (55.1 bar), 25°C (77°F), pH 8, Recovery 8%
- Permeate flow rates for individual elements may vary by ±15%

## Dimensions and Weight



Dimensions: mm (in)			Wet Weight: kg (lbs)
A	B	C	16 (35)
Element Length	Element O.D.	Core Tube I.D.	
1,016 (40)	200 (7.9)	28.6 (1.125)	

All dimensional information is indicative and for reference only. Please contact NanoH2O for detailed technical specifications.

## Operating Specifications

Specification	Unit	Value
Maximum Applied Pressure	psi (bar)	1,200 (82.7)
Maximum Chlorine Concentration	ppm	< 0.1
Maximum Operating Temperature	°C (°F)	45 (113)
pH Range, Continuous Operation		2–11
pH Range, Cleaning		2–13
Maximum Feed Water Turbidity	NTU	1.0
Maximum Feed Water SDI <sub>15</sub>		5.0
Maximum Feed Flow	gpm (m <sup>3</sup> /h)	75 (17)
Maximum Pressure Drop (ΔP) for Each Element	psi (bar)	15 (1.0)

These operating specifications are for general use. For specific applications, operation at more conservative values may ensure better performance and extended membrane life. See NanoH2O Technical Bulletins for more details.

The product performance is expressly conditioned on Buyer's storing, installing, operating, and maintaining Product in accordance with industry accepted good practices and Seller's written instructions provided in the Seller's Technical Manual may be viewed and downloaded at [www.nanoh2owater.com](http://www.nanoh2owater.com). The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. NanoH2O assumes no liability for results obtained or damages incurred through the application of the information contained

herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. All rights reserved. © NanoH2O Co., Ltd.

Please visit our website for regional contact information [www.nanoh2owater.com](http://www.nanoh2owater.com)